

DOZERS.

D150 | D180 | D255 | D350

Rugged and durable design | Longer undercarriage | Enhanced power and torque | High drawbar pull | Sealed and lubricated tracks | Dynamic braking effect | Ergonomically designed cab | Operator comfort | Easy maintenance and service



Model	D150	D180	D255	D350
Operating weight	14900 Kg	20530 Kg	27000 Kg	39100 Kg
Steering system	Hydrostatic / Power	Hydrostatic / Power	Hydrostatic / Power	Hydrostatic / Power
Power	116 kW	139 kW	177 kW	257 kW
Engine	Cummins	CNH	Cummins	Cummins
Max drawbar pull	275 Kn	290 Kn	450 Kn	576 Kn

EOSTRA
HOLDINGS LIMITED



BUILT AROUND YOU

SPECIFICATIONS

Model	D150	D180	D255	D350
Engine				
Net Power	116 kW	139 kW	177 kW	257 kW
Torque (max net)	690 Nm	860 Nm	1146 Nm	1674 Nm
Engine (make)	Cummins	CNH	Cummins	Cummins
Displacement	6.7 litres	6.7 litres	8.3 litres	10.82 litres
Cylinders	6	6	6	6
Bore & Stroke	104 x 132 mm	104 x 132 mm	114 x 135 mm	125 x 147 mm
Transmission				
Type	Hydrostatic drive	Power shift	Power shift	Power shift
Gears	1 forward / 1 reverse	3 forward / 3 reverse	3 forward / 3 reverse	3 forward / 3 reverse
Travel Speed (max)	13 km/h	11.3 km/h	10.9 km/h	10.6 km/h
Electrical System				
Number of batteries	2 - 24 V	2 - 24 V	2 - 24 V	2 - 24 V
Steering				
Type	Hydrostatic / Power	Hydrostatic / Power	Hydrostatic / Power	Hydrostatic / Power
Track				
Shoes	0.500 m	0.560 m	0.550 m	0.610 m
Gauge	1.900 m	1.900 m	2.070 m	2.134 m
Fluid Capacities				
Fuel Tank	246 litres	400 litres	500 litres	670 litres
Weights				
Operating Weight	14900 Kg	20530 Kg	27000 Kg	39100 Kg
Blade				
Type	SemiU	SemiU	SemiU	SemiU
Capacity	4.12 m ³	5.6 m ³	7.0 m ³	9.1 m ³
Width	3.2 m	3.46 m	3.8 m	3.97 m
Digging depth	480 mm	480 mm	530 mm	600 mm
Max lift above ground	900 mm	1100 mm	1220 mm	1220 mm
Ripper				
Type	Parallelogram	Parallelogram	Parallelogram	Parallelogram
Weight	1250 Kg	2010 Kg	3400 Kg	5140 Kg
Ripping depth	0.48 m	0.540 m	0.700 m	0.750 m
Ripping width	1.635 m	1.900 m	2.000 m	2.400 m
Shanks	3	3	3	1 or 3
Dimensions				
Transport length w/o attachment	4.065 m	4.195 m	4.490 m	5.282 m
Transport length with attachment	5.025 m	5.487 m	5.800 m	8.234 m
Transport height	3.0 m	3.235 m	3.420 m	3.500 m
Track				
Standard shoe width	500 mm	560 mm	550 mm	610 mm
Track on ground Length	2.985 m	2.700 m	2.973 m	3.243 m

13 PRODUCT FAMILIES • 80 BASE MODELS • OVER 600 CONFIGURATIONS

BRANCHES:

Bloemfontein | Cape Town | Durban | Johannesburg | Nelspruit | Port Elizabeth | Polokwane | Rustenburg



Finance and insurance options available on request.

FINANCE

National: 011 977 8300 | Customer Service: 0861 NEWHSA | Website: www.nhconstruction.co.za

