

DOZERS.

D150 | D180

Rugged and durable design | Longer undercarriage | Enhanced power and torque | High drawbar pull | Sealed and lubricated tracks | Dynamic braking effect | Ergonomically designed cab | Operator comfort | Easy maintenance and service



Model	D150	D180
Operating weight	14900 Kg	20530 Kg
Steering system	Hydrostatic / Power	Hydrostatic / Power
Power	116 kW	145 kW
Engine	Cummins	CNH
Max drawbar pull	275 Kn	290 Kn

EQSTRA
CONSTRUCTION EQUIPMENT



BUILT AROUND YOU

SPECIFICATIONS

Model	D150	D180
Engine		
Net Power	116 kW	145 kW
Torque (max net)	690 Nm	860 Nm
Engine (make)	Cummins	CNH
Displacement	6.7 litres	6.7 litres
Cylinders	6	6
Bore & Stroke	104 x 132 mm	104 x 132 mm
Transmission		
Type	Hydrostatic drive	Power shift
Gears	1 forward / 1 reverse	3 forward / 3 reverse
Travel Speed (max)	13 km/h	11.3 km/h
Electrical System		
Number of batteries	2 - 24 V	2 - 24 V
Steering		
Type	Hydrostatic / Power	Hydrostatic / Power
Track		
Shoes	0.500 m	0.560 m
Gauge	1.900 m	1.900 m
Fluid Capacities		
Fuel Tank	270 litres	400 litres
Weights		
Operating Weight	14900 Kg	20530 Kg
Blade		
Type	SemiU	SemiU
Capacity	4.12 m ³	5.6 m ³
Width	3.2 m	3.46 m
Digging depth	480 mm	480 mm
Max lift above ground	900 mm	1100 mm
Ripper		
Type	Parallelogram	Parallelogram
Weight	1552 Kg	2010 Kg
Ripping depth	0.48 m	0.540 m
Ripping width	1.8 m	1.900 m
Shanks	3	3
Dimensions		
Transport length w/o attachment	4.065 m	4.195 m
Transport length with attachment	5.025 m	5.487 m
Transport height	3.1 m	3.235 m
Track		
Standard shoe width	500 mm	560 mm
Track on ground Length	2.985 m	2.700 m

13 PRODUCT FAMILIES • 80 BASE MODELS • OVER 600 CONFIGURATIONS

BRANCHES:

Johannesburg | Durban | Port Elizabeth | Rustenburg | Kimberley | Kathu |
Cape Town | Middelburg | Polokwane



Finance and insurance options available on request.

National: 011 977 8300 | Customer Service: 0861 NEWHSA | Website: www.nhconstruction.co.za

